

393

Subdivision of Section 17, T. 24 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
72.25	Spur, slopes S. 60° E.; desc. 5 ft. over NE. slope.
72.45	Creek, 2 lks. wide, course S. 40° E.; asc. 135 ft. over SW. slope.
79.86	The ¼ sec. cor. of secs. 8 and 17.
	From the ¼ sec. cor. of secs. 16 and 17.
	N. 89° 43' W., on the E. and W. center line of sec. 17.
	Ascend 170 ft. over NE. slope, through heavy timber and dense undergrowth.
4.30	Ridge, bears N. 10° E. and S. 10° W., also enter logged area, edge bears same as ridge; desc. 425 ft. over NW. slope.
7.50	Gravelled road, 30 lks. wide, bears N. 10° W. and S. 10° E.
22.00	Ravine, drains N. 40° W.; asc. 100 ft. over NE. slope.
27.50	Spur ridge, bears N. 45° W. and S. 45° E.; desc. 275 ft. over broken W. slope.
38.55	Basin Creek, 10 lks. wide, course S. 25° W.; asc. 40 ft. over SE. slope.
39.80	Gravelled road, 40 lks. wide, bears N. 25° E. and S. 25° W.
40.14	The center ¼ sec. cor. of sec. 17.
	Ascend 25 ft. over SE. slope.
41.60	Spur, slopes S. 30° E.; desc. 5 ft. over SW. slope.
43.55	Gravelled road, 40 lks. wide, bears N. 50° W. and S. 50° E.
45.05	Creek, 5 lks. wide, course S. 45° E.; asc. 480 ft. over broken NE. slope.
60.23	Point for the center W 1/16 sec. cor. of sec. 17.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C} \frac{\text{W } 1/16}{\text{S } 17} \text{C} \\ 1976 \end{array}$
	from which
	A fir, 6 ins. diam., bears S. 3° W., 167 lks. dist., mkd. CW 1/16 S17 BT.
	A fir, 6 ins. diam., bears S. 26½° W., 148 lks. dist., mkd. X BT.
	Ascend 60 ft. over NE. slope.
62.50	Ridge, bears N. 70° W. and S. 40° E.; desc. 25 ft. over SW. slope.