

16013:

39

Subdivision of Section 17, T. 24 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
62.90	Gravelled road, 30 lks. wide, bears N. 60° W. and S. 60° E.
66.85	Bottom of descent, slopes S.; asc. 70 ft. over SE. slope.
69.25	Enter timber, edge bears N. 60° E. and S. 60° W.
72.05	Spur ridge, bears N. and S.; desc. 25 ft. over SW. slope.
73.90	Ravine, drains S. 10° E.; asc. 5 ft. over SE. slope.
74.95	Spur, slopes S. 10° W.; desc. 130 ft. over SW. slope.
79.85	Enter logged area, edge bears N. 5° W. and S. 5° E.
80.89	The ½ sec. cor. of secs. 17 and 18.
	From the center W 1/16 sec. cor. of sec. 17.
	N. 0° 38' E., on the N. and S. center line of the NW¼ of sec. 17.
	Descend 380 ft. over NE. slope, across logged area, through dense undergrowth.
13.30	Creek, 3 lks. wide, course S. 40° E.; asc. 275 ft. over SW. slope.
15.00	Gravelled road, 40 lks. wide, bears N. 30° W. and S. 35° E.
17.80	Enter timber, edge bears N. 45° W. and S. 45° E.
20.095	Point for the NW 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the NW¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW 1/16 S 17 1976
	from which
	A fir, 6 ins. diam., bears S. 40½° E., 47 lks. dist., mkd. NW 1/16 S17 BT.
	A fir, 10 ins. diam., bears N. 47° W., 67 lks. dist., mkd. NW 1/16 S17 BT.
	Ascend 75 ft. over SW. slope.
23.50	Spur ridge, bears N. 45° W. and S. 45° E.; desc. 30 ft. over NE. slope.
26.35	Dirt road, 30 lks. wide, bears N. 70° W. and S. 85° E.
30.50	Bottom of descent, slopes E.; asc. 235 ft. over SE. slope.
40.21	The W 1/16 sec. cor. of secs. 8 and 17.
	From the center N 1/16 sec. cor. of sec. 17.