

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	
R 8 W	R 7 W
S 13	S 18
S 24	S 19
1977	

from which

A fir, 5 ins. diam., bears N.  $64\frac{1}{2}^{\circ}$  E., 82 lks. dist., mkd. X BT.

A fir, 5 ins. diam., bears S.  $21\frac{1}{2}^{\circ}$  E., 45 lks. dist., mkd. T22S R7W S19 BT.

A fir, 5 ins. diam., bears S.  $44\frac{1}{2}^{\circ}$  W.,  $57\frac{1}{2}$  lks. dist., mkd. T22S R8W S24 BT.

A fir, 12 ins. diam., bears N.  $12\frac{1}{2}^{\circ}$  W.,  $77\frac{1}{2}$  lks. dist., mkd. T22S R8W S13 BT.

From this point, the cor. of secs. 7, 12, 13, and 18, bears N.  $0^{\circ} 14'$  W., 80.28 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S	
R 8 W	R 7 W
S 12	S 7
S 13	S 18
1968	

from which bearing trees mkd. by Ben B. Irving, Deputy County Surveyor, in 1929

A white oak, 24 ins. diam., bears S.  $65^{\circ}$  W., 309 lks. dist., with healed blaze.

A white oak, 34 ins. diam., bears S.  $79\frac{1}{2}^{\circ}$  W., 265 lks. dist., with healed blaze.

A white oak, 23 ins. diam., bears N.  $70\frac{1}{2}^{\circ}$  W., 287 lks. dist., with illegible scribe marks visible on partially healed blaze.

and a bearing tree mkd. by Milo Godfrey, Deputy County Surveyor, in 1962

A white fir, 22 ins. diam., bears N.  $59^{\circ}$  W., 311 lks. dist., with healed blaze.

From this same point, the cor. of secs. 19, 24, 25, and 30, bears S.  $0^{\circ} 14'$  E., 80.28 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 22 S	
R 8 W	R 7 W
S 24	S 19
S 25	S 30
1963	

from which the remains of the original bearing trees