

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

From this point, the NE. cor. of Claim No. 41, bears
N. $0^{\circ} 08' E.$, 20.41 chs. dist., hereinafter described.

Ascend 30 ft. over gentle SW. slope.

73.33

The witness cor. to secs. 17, 18, 19, and 20, perpetuated
and recorded by Wilford N. Haines, RLS No. 239, in 1967,
monumented with a steel rod, $\frac{1}{2}$ in. diam., firmly set,
projecting 1 in. above ground, from which the remains of
an original bearing tree:

A root hole, bears N. $28^{\circ} W.$, 92 lks. dist., with
a down fir alongside, 36 ins. diam., no marks
visible.

and a bearing tree mkd. by Haines

A fir, 15 ins. diam., bears West, $21\frac{1}{2}$ lks. dist.,
with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, directly over steel rod, with brass cap
mkd.

	W	C	
T 22	S	R 7	W
	S 18	S 17	→
	S 19	S 20	→
	1977		

from which a new bearing tree

A fir, 10 ins. diam., bears S. $59^{\circ} E.$, 40 lks.
dist., mkd. X BT.

Descend 115 ft. over precipitous E. slope.

78.33

True point for the cor. of secs. 17, 18, 19, and 20,
falls on precipitous E. slope, where it is impracticable
to establish a permanent monument.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 17 and 18,
bears N. $0^{\circ} 10' W.$, 39.95 chs. dist., perpetuated and
recorded by Wilford N. Haines, RLS No. 239, in 1961,
when original evidence was still in existence, monumented
with an iron rod, 1 in. diam., firmly set, projecting 6
ins. above ground, from which a bearing tree mkd. by
Haines:

A fir, 12 ins. diam., bears S. $88\frac{1}{2}^{\circ} E.$, 73 lks.
dist., with healed blaze.

and the remains of a bearing tree of which I have no
record

A sawed fir stump, 25 ins. diam., bears S. $33\frac{1}{2}^{\circ} E.$,
 $15\frac{1}{2}$ lks. dist., with scribe marks 4 S visible
on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, directly over iron rod, with brass cap
mkd.