

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">T 22 S R 7 W $\frac{1}{4}$ S 18 S 17 1977</p> <p>from which a new bearing tree</p> <p>A fir, 8 ins. diam., bears N. $71\frac{1}{2}^{\circ}$ W., 77$\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S18 BT.</p> <p>Land, rolling hills. Soil, sandy clay loam. Timber, fir, hemlock, cedar, madrone, alder, maple, chinquapin, and oak; undergrowth, hazel, huckleberry, vine maple, poison oak, rhododendron, blackberry, and fern.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, perpetuated and recorded by A. R. Evans, Deputy County Surveyor, in 1950, when original evidence was still in existence, and further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Godfrey:</p> <p>A fir, 18 ins. diam., bears N. $48\frac{1}{2}^{\circ}$ E., 53 lks. dist., with healed blaze.</p> <p>An oak, 9 ins. diam., bears N. 80° W., 91 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>
8.97	<p style="text-align: center;">T 22 S R 7 W $\frac{1}{4}$ S 19 S 20 1977</p> <p>N. $0^{\circ} 15'$ W., bet. secs. 19 and 20.</p> <p>Ascend 15 ft. along E. slope, through moderate timber and dense undergrowth.</p> <p>Intersect the N. bdy. of Donation Land Claim No. 39.</p> <p>Point for the crossing closing cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 S R 7 W CCC S 19 S 20 C 39 1977</p> <p>from which</p> <p>A fir, 9 ins. diam., bears N. $27\frac{1}{2}^{\circ}$ E., 7 lks. dist., mkd. T22S R7W S20 CCC BT.</p>