

T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 22 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by Aurelius Todd,
U. S. Deputy Surveyor, in 1894,
and the resurvey by Fred Mensch, Charles M. Collier,
and Fred W. Rodolf, U. S. Cadastral Engineers;
Elmer F. Strickler, U. S. Surveyor, and
Gerald A. Sorrels, U. S. Transitman, in 1919)

Beginning at the 1/4 sec. cor. of sec. 1 only, on the E.
bdy. of T. 22 S., R. 10 W., monumented with the original
sandstone, in place, 20 x 20 x 20 ins. (record, 16 x 12
x 6 ins.), above ground, mkd. 1/4 S1 on W. face, and X on
top, from which the remaining original bearing tree:

A fir, 67 ins. diam., bears S. 45° E., 76 lks.
dist., no marks visible on open blaze. (Record,
79 lks.)

and a bearing tree of which I have no record

A fir, 54 ins. diam., bears N. 64° E., 30 lks.
dist., no marks visible on open blaze.

At the corner point

Set a brass tablet, 3 1/2 ins. diam., 3 1/2 ins. stem, in a
drill hole, flush with the sandstone boulder, with top
mkd.

T 22 S |
R 10 W |
1/4 |
S 1 |
1974

from which new bearing trees

A fir, 16 ins. diam., bears S. 13° W., 58 lks.
dist., mkd. 1/4 S1 BT.

A fir, 22 ins. diam., bears N. 35° W., 26 lks.
dist., mkd. 1/4 S1 BT.

N. 0° 36' W., along the E. bdy. of sec. 1, marking and
blazing the true line.

Ascend 135 ft. along SW. slope, through moderate timber
and undergrowth.

- 6.00 Spur, slopes W.; desc. 250 ft. over NW. slope.
- 13.10 Little Mill Creek, 12 lks. wide, course S. 75° W.; asc.
30 ft. over SE. slope.
- 18.00 Spur, slopes E.; desc. 30 ft. over NW. slope.
- 20.00 Creek, 6 lks. wide, course S. 50° E.; asc. 255 ft. over
SE. slope.
- 35.90 Top of ascent, slopes E.; desc. 30 ft. over N. slope.
- 39.00 Creek, 3 lks. wide, course E.; asc. 10 ft. over SE. slope