

16028

Dependent Resurvey of a Portion of the East Boundary,
T. 22 S., R. 10 W., Willamette Meridian, Oregon

CHAINS															
40.95	<p>The closing cor. of T. 21 S., R. 10 W., and T. 22 S., R. 9 W., monumented with an unmarked sandstone, 16 x 10 x 8 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td>T 21 S</td></tr> <tr><td>T 22 S</td><td>R 10 W</td></tr> <tr><td>R 10 W</td><td>S 36 C</td></tr> <tr><td>S 1</td><td>S 6 C</td></tr> <tr><td></td><td>T 22 S</td></tr> <tr><td></td><td>R 9 W</td></tr> <tr><td></td><td>1974</td></tr> </table> <p>from which</p> <p>A cedar, 22 ins. diam., bears N. 32° E., 23 lks. dist., mkd. T21S R10W S36 CC BT.</p> <p>A hemlock, 13 ins. diam., bears S. 42° E., 87 lks. dist., mkd. T22S R9W S6 CC BT.</p> <p>Deposit corner stone alongside iron post.</p> <p>Ascend 10 ft. over SE. slope.</p>		T 21 S	T 22 S	R 10 W	R 10 W	S 36 C	S 1	S 6 C		T 22 S		R 9 W		1974
	T 21 S														
T 22 S	R 10 W														
R 10 W	S 36 C														
S 1	S 6 C														
	T 22 S														
	R 9 W														
	1974														
41.25	<p>An original line object, a sandstone, 8 x 8 x 6 ft. above ground, mkd. X on N. face. This now becomes an angle point.</p> <p>from which</p> <p>A fir, 45 ins. diam., bears S. 31½° W., 184 lks. dist., mkd. AP S1 BT.</p> <p>A fir, 19 ins. diam., bears N. 44½° W., 37 lks. dist., mkd. AP S1 BT.</p>														
	<p>N. 0° 07' W., beginning new measurement.</p> <p>Ascend 15 ft. over SE. slope.</p>														
12.00	<p>Dirt road, 15 lks. wide, bears N. 70° E. and N. 15° W., in curve.</p>														
12.42	<p>The NE. cor. of T. 22 S., R. 10 W., monumented with a sandstone, 14 x 12 x 6 ins., firmly set, projecting 8 ins. above ground, mkd. with 6 notches on S. and W. edges, alongside of which is a steel fence post, firmly set, projecting 3 ft. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>														