

16030

Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	N. 89° 53' W., along the S. bdy. of sec. 31, marking and blazing the true line.
	Descend 110 ft. over SW. slope, through moderate timber and undergrowth.
3.11	True point for the closing cor. of secs. 5 and 6, T. 22 S., R. 9 W., hereinafter described.
	Descend 125 ft. over SW. slope.
4.75	Dry creek bed, 2 lks. wide, drains S.; asc. 100 ft. along S. slope.
23.12	Point for the E 1/16 sec. cor. of sec. 6 only. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <u>E 1/16 S 6</u> T 22 S R 9 W 1974 </div>
	from which
	A fir, 21 ins. diam., bears S. 30° E., 5 lks. dist., mkd. E 1/16 S6 BT.
	A fir, 30 ins. diam., bears S. 68° W., 65 lks. dist., mkd. E 1/16 S6 BT.
	Corner is located at top of ascent, slopes generally SE.; desc. 230 ft. over SW. slope.
28.50	Creek, 2 lks. wide, course S. 15° W.; asc. 300 ft. over SE. slope.
39.92	Point for the ¼ sec. cor. of sec. 31 only, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T 21 S R 9 W <u>¼ S 31</u> 1974 </div>
	from which
	A fir, 30 ins. diam., bears N. 74½° E., 78 lks. dist., mkd. ¼ S31 BT.
	A fir, 22 ins. diam., bears N. 55½° E., 140 lks. dist., mkd. ¼ S31 BT.
	Ascend 50 ft. over SE. slope.
43.13	Point for the ¼ sec. cor. of sec. 6 only, at proportionate distance.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <u>¼ S 6</u> T 22 S R 9 W 1974 </div>