

Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 19 ins. diam., bears S.  $56\frac{1}{2}^{\circ}$  E.,  $56\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{2}$  S6 BT.

A fir, 16 ins. diam., bears West, 95 lks. dist., mkd.  $\frac{1}{2}$  S6 BT.

Ascend 300 ft. over SE. slope.

57.10 Ridge, bears N.  $25^{\circ}$  E. and S.  $25^{\circ}$  W.; desc. 210 ft. over NW. slope.

62.10 Ravine, drains N.  $25^{\circ}$  W.; asc. 40 ft. over NE. slope.

70.00 Spur, slopes N.; desc. 210 ft. over NW. slope.

76.30 Ravine, drains N.; desc. 25 ft. over NE. slope.

78.25 Top of ascent, slopes S.  $80^{\circ}$  W.; desc. 25 ft. over W. slope.

79.84 The cor. of Tps. 21 S., Rs. 9 and 10 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

|        |       |
|--------|-------|
| T 21 S |       |
| R 10 W | R 9 W |
| S 36   | S 31  |
| 1919   |       |

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N.  $19^{\circ}$  E., 32 lks. dist., no marks visible.  
(Record, N.  $46^{\circ}$  E., 27 lks.)

and a bearing tree mkd. by Mensch, Collier, Rodolf, Strickler, and Sorrels, in 1919

A fir, 28 ins. diam., bears N.  $46^{\circ}$  W., 48 lks. dist., with healed blaze. (Record, N.  $19^{\circ}$  W.)

and new bearing trees

A fir, 10 ins. diam., bears N.  $29^{\circ}$  E., 55 lks. dist., mkd. T21S R9W S31 BT.

A fir, 20 ins. diam., bears N.  $89^{\circ}$  W., 60 lks. dist., mkd. T21S R9W S36 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, and madrone; undergrowth, fern, salal, Oregon grape, blackberry, poison oak, scotch broom, and rhododendron.

Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by Alonzo Gesner,  
U. S. Deputy Surveyor, in 1894,  
and the resurvey by Fred Mensch, Charles M. Collier,  
and Fred W. Rodolf, U. S. Cadastral Engineers;  
Elmer F. Strickler, U. S. Surveyor, and  
Gerald A. Sorrels, U. S. Transitman, in 1919)