

16032

Dependent Resurvey of a Portion of the South Boundary,  
T. 21 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
5.80	<p>S. 89° 05' W., along the S. bdy. of sec. 36, marking and blazing the true line.</p> <p>Descend 200 ft. over SW. slope, through moderate timber and undergrowth.</p>
13.23	<p>Little Mill Creek, 5 lks. wide, course S. 45° W.; asc. 5 ft. over SE. slope.</p> <p>Intersect the E. bdy. of T. 22 S., R. 10 W.</p> <p>The closing cor. of T. 21 S., R. 10 W. and T. 22 S., R. 9 W., hereinbefore described.</p> <p>From this point, the angle point on the E. bdy. of sec. 1, T. 22 S., R. 10 W., bears N. 0° 36' W., 0.30 chs. dist., hereinbefore described.</p> <p>Land, mountainous. Soil, sandy loam and rocky clay. Timber, fir, hemlock, cedar, maple, and alder; undergrowth, salal, Oregon grape, blackberry, fern, vine maple, and poison oak.</p>
<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 22 S., R. 9 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the survey by William H. Byars, U. S. Deputy Surveyor, in 1874 and 1878, and the survey and resurvey by Elmer O. Worrick, U. S. Deputy Surveyor, in 1894-95)</p>	
<p>From the cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1967, monumented with an iron rod, 5/8 in. diam., firmly set flush with the surface of Lutsinger Creek Road, gravelled, 30 lks. wide, bears N. 50° W. and S. 30° E., in curve, from which the remains of an original bearing tree:</p>	
<p>A decayed fir stump, 20 ins. diam., bears N. 54° E., 62 lks. dist., no marks visible. (Record, 67 lks.)</p>	
<p>and reference monuments</p>	
<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 28° E., 50 lks. dist., with brass cap mkd. RM T22S R9W S24 33 ft. 1974, and an arrow pointing to the corner.</p>	
<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 28° W., 50 lks. dist., with brass cap mkd. RM T22S R9W S23 33 ft. 1974, and an arrow pointing to the corner.</p>	
<p>From this point, a witness cor. established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1967, bears East, 0.380 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T22S R9W S23 S24 S25 S26 WC, and an arrow pointing to the corner.</p>	