

16034

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
4.10	Lutsinger Creek, 10 lks. wide, course N. 40° E.; asc. 10 ft. over SE. slope.
6.70	Creek, 5 lks. wide, course E.; asc. 145 ft. over SE. slope, changing to S. slope.
12.45	Dirt road, 10 lks. wide, bears N. 65° E. and S. 80° W.; in curve.
20.67	Point for the N 1/16 sec. cor. of secs. 23 and 24. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> N 1/16 S 23 S 24 1973 </div> from which A maple, 14 ins. diam., bears S. 74½° E., 38 lks. dist., mkd. N 1/16 S24 BT. A fir, 12 ins. diam., bears S. 84¾° W., 17 lks. dist., mkd. N 1/16 S23 BT. Ascend 60 ft. over SE. slope.
35.20	Abandoned dirt road, 10 lks. wide, bears N. 20° E. and S. 20° W.
41.34	The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, monumented with an iron pin, 1 in. diam., firmly set, projecting 2 ins. above ground, from which the only remaining original bearing tree: A fir, 40 ins. diam., bears N. 23° E., 8 lks. dist., with scribe marks T22S R9W S BT visible on portion of decayed blaze lying alongside, (Record, S. 23° E.) At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pin, with brass cap mkd. <div style="text-align: center;"> T 22 S R 9 W S 14 S 13 S 23 S 24 1973 </div> from which new bearing trees A fir, 11 ins. diam., bears N. 79° E., 84 lks. dist., mkd. T22S R9W S13 BT. A maple, 10 ins. diam., bears S. 44° E., 35 lks. dist., mkd. T22S R9W S24 BT. A fir, 10 ins. diam., bears S. 85° W., 64 lks. dist., mkd. T22S R9W S23 BT. A fir, 10 ins. diam., bears N. 51° W., 50 lks. dist., mkd. T22S R9W S14 BT. Land, rolling hills. Soil, sandy clay and loam.