

Dependent Resurvey, Portion of Subdivisional Lines
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Timber, fir, hemlock, cedar, maple, alder, and madrone; undergrowth, fern, salal, Oregon grape, vine maple, poison oak, rhododendron, and scotch broom.

From the cor. of secs. 27 and 35 only, on the W. bdy. of sec. 26, perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S
S 27 | S 26
S 35 |
R 9 W
1968

from which the remains of the original bearing trees

A root hole, bears N. 55° E., 74 lks. dist., with a down fir alongside, size indeterminate, no marks visible.

A fir, 50 ins. diam., bears S. 62° W., 91 lks. dist., no marks visible on open blaze.

A fir, 41 ins. diam., bears N. 66° W., 21 lks. dist., with healed blaze.

and bearing trees mkd. by Tracy

A hemlock, 13 ins. diam., bears N. 34° E., 53 lks. dist., with scribe marks T22S R9W CS BT visible on partially healed blaze.

A hemlock, 13 ins. diam., bears S. 77° W., 122 lks. dist., with scribe marks T22S R9W visible on partially healed blaze.

A hemlock, 11 ins. diam., bears N. 52° W., 60 lks. dist., with illegible scribe marks visible on partially healed blaze.

N. 0° 41' W., bet. secs. 26 and 27.

Ascend 200 ft. over SE. slope, through moderate timber and undergrowth.

4.45 Spur, slopes E.; desc. 100 ft. over N. slope.

5.15 Dry creek bed, 10 lks. wide, drains S. 50° E.; asc. 340 ft. over SE. slope.

17.45 Spur, slopes E.; desc. 20 ft. over NE. slope.

22.55 Ravine, drains S. 60° E.; asc. 325 ft. over steep SE. slope.

29.55 Dirt road, 15 lks. wide, bears N. 40° E. and S. 75° W., in curve.

33.93 Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.