

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	T 22 S R 9 W. $\frac{1}{2}$ S 27   S 26 1974
	from which  A fir, 14 ins. diam., bears N. 38° E., 19 lks. dist., mkd. $\frac{1}{2}$ S26 BT.  A fir, 14 ins. diam., bears S. 42½° W., 28 lks. dist., mkd. $\frac{1}{2}$ S27 BT.  From this point, a point established by person(s) unknown bears S. 19° W., 70 lks. dist., monumented with an iron pipe, 2½ ins. diam., firmly set, projecting 6 ins. above ground.  Ascend 50 ft. over SE. slope.
34.55	Ridge, bears N. 70° E. and S. 70° W.; desc. 125 ft. over NE. slope.
40.25	Ravine, drains N. 45° W.; asc. 50 ft. over SW. slope.
48.75	Spur, slopes W.; desc. 200 ft. over NW. slope.
65.85	Ravine, drains N. 70° W.; asc. 30 ft. over SW. slope.
70.65	Top of ascent, slopes N. 70° W.; desc. 65 ft. over NW. slope.
73.85	Point for the cor. of secs. 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 22 S R 9 W S 22   S 23 S 27   S 26 1974
	from which  A fir, 8 ins. diam., bears N. 63° E., 22 lks. dist., mkd. T22S R9W S23 BT.  A fir, 20 ins. diam., bears S. 75° E., 22 lks. dist., mkd. T22S R9W S26 BT.  A fir, 22 ins. diam., bears S. 54° W., 11 lks. dist., mkd. T22S R9W S27 BT.  A fir, 12 ins. diam., bears N. 49° W., 14 lks. dist., mkd. T22S R9W S22 BT.  Land, mountainous. Soil, rocky clay and loam. Timber, fir, hemlock, cedar, maple, alder, and madrone; undergrowth, fern, salal, vine maple, scotch broom, rhododendron, Oregon grape, and poison oak.
	From the cor. of secs. 23, 24, 25, and 26.