

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	S. 88° 48' W., bet. secs. 23 and 26.
	Descend 35 ft. over general W. slope, across open grassy field.
6.35	Lutsinger Creek, 25 lks. wide, course N. 50° W.; leave open grassy field, enter moderate timber and undergrowth, edge bears generally N. and S.; asc. 220 ft. over SE. slope.
17.20	Spur, slopes N. 35° E.; desc. 30 ft. over NW. slope.
19.815	Point for the E 1/16 sec. cor. of secs. 23 and 26.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 23}{\text{S } 26} \\ 1974 \end{array}$
	from which
	A fir, 16 ins. diam., bears N. 49½° W., 58 lks. dist., mkd. E 1/16 S23 BT.
	A fir, 18 ins. diam., bears S. 77½° E., 54 lks. dist., mkd. E 1/16 S26 BT.
	Descend 60 ft. over NW. slope.
24.00	Creek, 5 lks. wide, course N. 45° E.; asc. 260 ft. over SE. slope.
39.63	The ¼ sec. cor. of secs. 23 and 26, monumented with a sandstone, 12 x 12 x 8 ins., firmly set 8 ins. in the ground, mkd. ¼ on N. face, from which the remains of bearing trees mkd. by Worrick:
	A decayed fir stump, 30 ins. diam., bears N. 18° W., 35 lks. dist., with scribe marks BT visible on opened blaze.
	A maple, 30 ins. diam., bears S. 6° E., 25 lks. dist., with healed blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T } 22 \text{ S } \text{R } 9 \text{ W} \\ \frac{1}{4} \quad \frac{\text{S } 23}{\text{S } 26} \\ 1974 \end{array}$
	from which new bearing trees
	A fir, 12 ins. diam., bears N. 49½° E., 59 lks. dist., mkd. ¼ S23 BT.
	A fir, 9 ins. diam., bears S. 82° E., 35 lks. dist., mkd. ¼ S26 BT.
	Deposit corner stone alongside iron post.