

16038

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	N. 89° 02' W., beginning new measurement.
	Ascend 70 ft. over SE. slope, across sandstone outcropping facing S., through moderate timber and undergrowth.
6.60	Leave sandstone outcropping, slopes sharply S.; asc. 60 ft. over SE. slope.
8.10	Spur, slopes S. 25° E.; desc. 70 ft. over SW. slope.
10.60	Ravine, drains S. 20° E.; asc. 25 ft. over steep SE. slope.
13.90	Spur, slopes S. 30° E.; desc. 125 ft. over SW. slope.
21.70	Ravine, drains S. 30° E.; asc. 330 ft. over steep SE. slope.
32.40	Ridge, bears N. 30° E. and S. 30° W.; desc. 290 ft. over steep W. slope.
40.41	The cor. of secs. 22, 23, 26, and 27.
	Land, mountainous. Soil, rocky clay and loam. Timber, fir, hemlock, cedar, maple, alder, and madrone; undergrowth, fern, salal, vine maple, scotch broom, rhododendron, Oregon grape, and poison oak.
	N. 0° 14' E., bet. secs. 22 and 23.
	Ascend 15 ft. along W. slope, through moderate timber and undergrowth.
8.30	Top of ascent, slopes W.; desc. 30 ft. over NW. slope.
10.40	Ravine, drains N. 50° W.; desc. 10 ft. over NW. slope.
15.00	Ravine, drains S. 70° W.; desc. 60 ft. over NW. slope.
19.96	Point for the S 1/16 sec. cor. of secs. 22 and 23.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 22 S 23 1974
	from which
	A fir, 12 ins. diam., bears S. 35° E., 4 lks. dist., mkd. S 1/16 S23 BT.
	A fir, 10 ins. diam., bears S. 21½° W., 8½ lks. dist., mkd. S 1/16 S22 BT.
	Corner is located at bottom of descent, slopes W.; asc. 50 ft. over SW. slope.
23.20	Top of ascent, slopes N. 60° W.; desc. 145 ft. over NW. slope.
34.60	Spur, slopes W.; desc. 50 ft. over steep NW. slope.
38.00	Abandoned dirt road, 10 lks. wide, bears N. 80° E. and S. 80° W.