

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
39.92	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W $\frac{1}{4}$ S 22 S 23 1974</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. $19\frac{1}{2}^{\circ}$ E., 105 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p style="padding-left: 40px;">A hemlock, 25 ins. diam., bears N. 12° W., 56 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>Descend 20 ft. over NW. slope.</p>
40.20	<p>Bottom of descent, drains N. 75° W., also abandoned dirt road, 10 lks. wide, bears N. 75° W. and S. 30° W., in curve; asc. 145 ft. over SW. slope.</p>
59.88	<p>Point for the N $1/16$ sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N $1/16$ S 22 S 23 1974</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 76° E., 58 lks. dist., mkd. N $1/16$ S23 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ W., 18 lks. dist., mkd. N $1/16$ S22 BT.</p> <p>Corner is located at top of ascent, slopes generally W.; desc. 290 ft. over NW. slope.</p>
69.00	<p>Creek, 1 lk. wide, course N. 35° W.; asc. 15 ft. over SW. slope.</p>
74.90	<p>Top of ascent, slopes W.; desc. 65 ft. over NW. slope.</p>
78.75	<p>Creek, 10 lks. wide, course N. 75° W.; asc. 110 ft. over steep SW. slope.</p>
79.84	<p>The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, monumented with an iron rod, $5/8$ in. diam., firmly set, projecting 4 ins. above ground, subsequently remonumented by Vernon R. Tracy, Deputy County Surveyor, in 1968, with an iron post, 2 ins. diam., lying alongside, with brass cap mkd. COUNTY SURVEYORS OFFICE T22S S14 S15 S22 S23 R9W 1968, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A fir, 45 ins. diam., bears N. 65° E., 32 lks. dist., with healed blaze.</p>