

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS
19.42

Point for the E 1/16 sec. cor. of sec. 34 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16 S 34
1974

from which

A fir, 8 ins. diam., bears S. 73° W., 13 lks. dist., mkd. E 1/16 S34 BT.

No other suitable tree available within limits.

Ascend 90 ft. over NE. slope.

23.50 Ridge, bears S. 25° E. and N. 25° W.; desc. 140 ft. over NW. slope.

27.80 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.

30.27 Point for the ¼ sec. cor. of sec. 27 only, at midpoint longitudinally on the S. bdy. of sec. 27.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
¼ S 27
1974

from which

A fir, 9 ins. diam., bears N. 67° E., 35 lks. dist., mkd. ¼ S27 BT.

A fir, 10 ins. diam., bears N. 37½° W., 16 lks. dist., mkd. ¼ S27 BT.

Descend 120 ft. over NW. slope.

38.84 The ¼ sec. cor. of sec. 34 only, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 22 S
¼ S 34
R 9 W
1968

from which the remains of the original bearing trees

A fir, 36 ins. diam., bears N. 50° E., 51 lks. dist., with axe mark X visible on SE. and SW. faces.

A fir snag, 60 ins. diam., bears S. 20° E., 60 lks. dist., no marks visible.

and bearing trees mkd. by Tracy

A hemlock, 12 ins. diam., bears S. 9° E., 23 lks. dist., with scribe marks ¼ S34 CS BT visible on partially healed blaze.