

16044

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 8 ins. diam., bears S. 81° W., 23 lks. dist., with healed blaze.</p> <hr/> <p>N. 84° 27' W., beginning new measurement.</p> <p>Descend 80 ft. over NW. slope.</p>
2.55	Ravine, drains NW.; desc. 10 ft. over NW. slope.
6.70	Spur, slopes N. 10° E.; desc. 370 ft. over NW. slope.
14.70	Rock bluff, 20 ft. high, faces S.
16.50	Creek, 1 lk. wide, course S. 70° W.; asc. 70 ft. over SE. slope.
21.50	Spur, slopes S.; desc. 70 ft. over SW. slope.
26.20	Creek, 2 lks. wide, course S. 45° E.; asc. 300 ft. over NE. slope.
31.06	True point for the closing cor. of secs. 27 and 28, hereinafter described.
	Ascend 80 ft. over NE. slope.
38.69	<p>The cor. of secs. 33 and 34 only, determined at record bearing and distance from the remains of the original bearing trees:</p> <p>A sawed fir stump, 50 ins. diam., bears S. 15° E., 95 lks. dist., with scribe marks BT visible on open blaze.</p> <p>A sawed fir stump, 50 ins. diam., bears S. 40° W., 115 lks. dist., with scribe marks R9W BT visible on bark blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 9 W</p> <p>S 28</p> <hr style="width: 50%; margin: auto;"/> <p>S 33   S 34</p> <p>1974</p> </div> <p>No suitable trees available within limits.</p> <p>Land, mountainous.</p> <p>Soil, rocky clay.</p> <p>Timber, fir, cedar, hemlock, cherry, alder, maple, and chinquapin; undergrowth, vine maple, hazel, devil's club, blackberry, huckleberry, elderberry, fern, salal, Oregon grape, arrowwood, and thimbleberry.</p>
4.50	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 88° 59' W., bet. secs. 22 and 27.</p> <p>Descend 150 ft. over NW. slope, through moderate timber and undergrowth.</p> <p>Ravine, drains N. 35° W.; desc. 170 ft. over NW. slope.</p>