

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
12.80	Creek, 5 lks. wide, course N. 10° E.; asc. 250 ft. over E. slope.
19.83	Point for the E 1/16 sec. cor. of secs. 22 and 27. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \text{ } \frac{\text{S } 22}{\text{S } 27} \\ 1975 \end{array}$ </div> from which A fir, 15 ins. diam., bears N. 52° E., 105 lks. dist., mkd. E 1/16 S22 BT. A fir, 19 ins. diam., bears S. 28° E., 53 lks. dist., mkd. E 1/16 S27 BT. Corner is located on spur, slopes N.; desc. 20 ft. over NW. slope.
21.10	Creek, 2 lks. wide, course N. 60° E.; asc. 200 ft. over general E. slope.
32.60	Spur, slopes N.; desc. 90 ft. over NW. slope.
34.00	Bottom of descent, slopes N.; asc. 110 ft. over NE. slope.
36.50	Spur, slopes N. 50° E.; desc. 125 ft. over steep NW. slope.
39.66	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} \text{T } 22 \text{ S } \text{R } 9 \text{ W} \\ \frac{1}{4} \frac{\text{S } 22}{\text{S } 27} \\ 1975 \end{array}$ </div> from which A fir, 34 ins. diam., bears N. 37½° W., 15 lks. dist., mkd. ¼ S22 BT. A fir, 21 ins. diam., bears S. 5½° W., 73 lks. dist., mkd. ¼ S27 BT. Descend 85 ft. over NW. slope.
41.30	Creek, 2 lks. wide, drains NW.; desc. 100 ft. over NW. slope.
42.90	Creek, 10 lks. wide, course N. 5° W.; asc. 200 ft. over NE. slope.
52.30	Ridge, bears N. 20° W. and S. 20° E.; desc. 520 ft. over W. slope.
77.50	Creek, 5 lks. wide, course N.; asc. 100 ft. over E. slope.