

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 32 ins. diam., bears N. 45° W., 49 lks. dist., with healed blaze. (Record, 52 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W S 28 S 27 1975</p> <p>from which new bearing trees</p> <p>A fir, 32 ins. diam., bears S. 30° E., 15 lks. dist., mkd. ¼ S27 BT.</p> <p>A fir, 26 ins. diam., bears West, 106 lks. dist., mkd. ¼ S28 BT.</p> <p>Deposit corner stone alongside iron post.</p> <p>S. 1° 16' E., beginning new measurement.</p> <p>Ascend 300 ft. over N. slope.</p>
3.60	Ridge, bears N. 70° E. and S. 70° W.; desc. 400 ft. over S. slope.
5.90	Dirt road, 25 lks. wide, bears N. 75° E. and S. 75° W.
19.45	Point for the S 1/16 sec. cor. of secs. 27 and 28.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 28 S 27 1975</p> <p>from which</p> <p>A fir, 12 ins. diam., bears S. 63¼° E., 17 lks. dist., mkd. S 1/16 S27 BT.</p> <p>A fir, 18 ins. diam., bears S. 56¼° W., 84 lks. dist., mkd. S 1/16 S28 BT.</p> <p>Descend 120 ft. over S. slope, changing to SE. slope.</p>
20.80	Creek, 1 lk. wide, course S. 20° E.; desc. 70 ft. over SE. slope.
24.60	Creek, 3 lks. wide, course SE.; asc. 70 ft. over NE. slope.
26.00	Spur, slopes S. 75° E.; desc. 60 ft. over SE. slope.
27.00	Creek, 5 lks. wide, course S. 85° E.; asc. 60 ft. over N. slope.
33.46	<p>The original closing cor. of secs. 27 and 28, determined from the remains of the original bearing trees:</p> <p>A fir, 20 ins. diam., bears N. 9° E., 104 lks. dist., no marks visible on decayed blaze. (Record, 100 lks.)</p>