

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p>A fir, 35 ins. diam., bears S. 57° E., 45 lks. dist., mkd. S 1/16 S22 BT.</p> <p>A fir, 28 ins. diam., bears S. 9° W., 39 lks. dist., mkd. S 1/16 S21 BT.</p> <p>Ascend 200 ft. over steep S. slope.</p>
34.40	Spur, slopes N. 35° E.; desc. 200 ft. over general NW. slope.
39.34	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W $\frac{1}{4}$ S 21 S 22 1975</p>
	<p>from which</p> <p>A fir, 12 ins. diam., bears N. 36° E., 62 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>A fir, 17 ins. diam., bears N. 50° W., 24 lks. dist., mkd. $\frac{1}{4}$ S21 BT.</p> <p>Descend 150 ft. over N. slope.</p>
45.10	Creek, 8 lks. wide, course N. 65° E.; asc. 90 ft. over general S. slope.
51.80	Creek, 1 lk. wide, course S. 30° E.; asc. 380 ft. over SW. slope.
59.01	<p>Point for the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 21 S 22 1975</p>
	<p>from which</p> <p>A fir, 22 ins. diam., bears S. 78$\frac{1}{2}$° E., 39 lks. dist., mkd. N 1/16 S22 BT.</p> <p>A fir, 18 ins. diam., bears S. 42$\frac{3}{4}$° W., 38 lks. dist., mkd. N 1/16 S21 BT.</p> <p>Ascend 135 ft. over general S. slope.</p>
73.70	Spur, slopes SE.; desc. 140 ft. over NE. slope.
77.70	Bottom of descent, drains SE.; asc. 15 ft. over general S. slope.