

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
19.20	Spur, slopes N.; desc. 15 ft. over NW. slope.
19.98	Point for the E 1/16 sec. cor. of secs. 15 and 22. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{E } 1/16 \quad \frac{\text{S } 15}{\text{S } 22} \\ 1975 \end{array}$ from which A fir, 13 ins. diam., bears N. 43½° W., 46 lks. dist., mkd. E 1/16 S15 BT. A fir, 18 ins. diam., bears S. 1° E., 54 lks. dist., mkd. E 1/16 S22 BT. Descend 5 ft. over NW. slope.
20.40	Ravine, drains N.; desc. 160 ft. over W. slope.
28.40	Creek, 4 lks. wide, course N.; asc. 125 ft. over SE. slope.
36.85	Ravine, drains S.; asc. 95 ft. over SE. slope.
39.96	Point for the ¼ sec. cor. of secs. 15 and 22, at porportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{T } 22 \text{ S } \text{R } 9 \text{ W} \\ \frac{1}{4} \quad \frac{\text{S } 15}{\text{S } 22} \\ 1975 \end{array}$ from which A fir, 19 ins. diam., bears N. 17° E., 8 lks. dist., mkd. ¼ S15 BT. A fir, 22 ins. diam., bears S. 16° E., 27 lks. dist., mkd. ¼ S22 BT. Ascend 2 ft. over SE. slope.
40.60	Spur, slopes S. 20° W.; desc. 15 ft. over W. slope.
42.35	Ravine, drains S. 40° E.; asc. 160 ft. over E. slope.
46.30	Spur, slopes S. 25° E.; desc. 45 ft. over SW. slope.
49.40	Ravine, drains S. 25° E.; asc. 265 ft. over SE. slope.
57.00	Spur, slopes S. 30° E.; desc. 65 ft. over SW. slope.
59.94	Point for the W 1/16 sec. cor. of secs. 15 and 22. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{c} \text{W } 1/16 \quad \frac{\text{S } 15}{\text{S } 22} \\ 1975 \end{array}$