

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p>A fir, 8 ins. diam.; bears S. 82° E., 46 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p> <p>A fir, 17 ins. diam., bears S. 60° W., 34 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p> <p>Ascend 5 ft. over SE. slope.</p>
39.80	Top of ascent, slopes S.; desc. 60 ft. over broken SW. slope.
45.40	Ravine, drains S.; asc. 135 ft. over SE. slope.
50.95	Spur, slopes S.; desc. 30 ft. over SW. slope.
53.13	Point for the W 1/16 sec. cor. of sec. 28 only.
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W W 1/16 S 28 1975</p>
	<p>from which</p> <p>A fir, 7 ins. diam., bears N. 41° E., 23 lks. dist., mkd. W 1/16 S28 BT.</p> <p>A fir, 8 ins. diam., bears N. $\frac{1}{2}$° W., 55 lks. dist., mkd. W 1/16 S28 BT.</p> <p>Descend 10 ft. over SW. slope.</p>
53.70	Head of ravine, drains S.; asc. 350 ft. over SE. slope.
70.15	Spur, slopes S.; desc. 95 ft. over SW. slope.
72.63	True point for the closing cor. of secs. 28 and 29, hereinafter described.
	Descend 120 ft. over SW. slope.
73.75	Dirt road, 20 lks. wide, bears S. 15° E. and N. 15° W.
75.60	Ravine, drains S. 35° W.; asc. 20 ft. along broken S. slope.
78.22	<p>The cor. of secs. 32 and 33 only, perpetuated by person (s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. S29 S32 S33, from which the remains of the original bearing trees:</p> <p>A burned and decayed fir stump, 34 ins. diam., bears N. 85° E., 52 lks. dist., no marks visible.</p> <p>A burned fir stump, 60 ins. diam., bears S. 35° E., 60 lks. dist., no marks visible. (Record, S. 25° E.)</p> <p>A decayed fir stump, size indeterminate, bears S. 20° W., 24 lks. dist., no marks visible.</p> <p>A burned fir stump, 20 ins. diam., bears N. 36° W., 37 lks. dist., no marks visible.</p>