

16054

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins.diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W S 29 S 32   S 33 1975</p> <p>from which new bearing trees</p> <p>A fir, 18 ins. diam., bears S. 35° E., 9 lks. dist., mkd. T22S R9W S33 BT.</p> <p>A fir, 11 ins. diam., bears S. 89° W., 58 lks. dist., mkd. T22S R9W S32 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, alder, maple, chinquapin, and hemlock; undergrowth, poison oak, vine maple, salmonberry, blackberry, huckleberry, hazel, devil's club, Oregon grape, salal, and fern.</p>
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89° 24' W., bet. secs. 21 and 28.</p> <p>Ascend 50 ft. over E. slope, through moderate timber and undergrowth.</p> <p>5.40 Ravine, drains N. 60° E.; asc. 150 ft. over E. slope.</p> <p>8.20 Spur, slopes N. 30° E.; desc. 75 ft. over W. slope.</p> <p>10.70 Ravine, drains N. 20° E.; asc. 120 ft. over NE. slope.</p> <p>15.40 Spur, slopes N. 10° W.; desc. 200 ft. over SW. slope.</p> <p>21.51 Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W E 1/16 S 21 S 28 1975</p> <p>from which</p> <p>A fir, 20 ins. diam., bears N. 31° E., 50 lks. dist., mkd. E 1/16 S21 BT.</p> <p>A fir, 46 ins. diam., bears S. 68° E., 122 lks. dist., mkd. E 1/16 S28 BT.</p> <p>Descend 170 ft. over SW. slope.</p> <p>26.60 Creek, 2 lks. wide, course N. 65° W.; desc. 50 ft. over NW. slope.</p> <p>28.10 Creek, 10 lks. wide, course N. 10° W.; asc. 200 ft. over NE. slope.</p>