

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS
40.76

The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, determined at record distance from the original bearing trees:

A fir, 55 ins. diam., bears N. 15° E., 55 lks. dist., with illegible scribe marks visible on open blaze. (Record, N. $22\frac{1}{2}^{\circ}$ W.)

A fir, 41 ins. diam., bears S. $22\frac{1}{2}^{\circ}$ E., 31 lks. dist., with healed blaze. (Record, S. 15° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
 $\frac{1}{4}$ $\frac{S 21}{S 28}$
1975

N. $89^{\circ} 09'$ W., beginning new measurement.

Ascend 400 ft. over broken NE. slope.

22.30 Dirt road, 20 lks. wide, bears N. and S.

29.15 Spur, slopes NW.; desc. 295 ft. over SW. slope.

38.20 Ravine, drains S. 30° W.; desc. 55 ft. along S. slope.

39.43 The cor. of secs. 20, 21, 28, and 29, perpetuated by person(s) unknown, monumented with a wooden stake, 1 in. diam., firmly set, projecting 2 ins. above ground, from which the only remaining original bearing tree:

A fir, 27 ins. diam., bears N. 8° E., 49 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
S 20 | S 21
S 29 | S 28
1975

from which new bearing trees

A fir, 8 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., 29 lks. dist., mkd. T22S R9W S28 BT.

A hemlock, 9 ins. diam., bears S. 37° W., 36 lks. dist., mkd. T22S R9W S29 BT.

A fir, 23 ins. diam., bears N. $13\frac{1}{2}^{\circ}$ W., 144 lks. dist., mkd. T22S R9W S20 BT.

Reset wooden stake alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, chinquapin, madrone, maple, alder, and yew; undergrowth, fern, vine maple, salal, Oregon grape, salmonberry, rhododendron, scotch broom, and poison oak.