

16056

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	S. 0° 49' E., bet. secs. 28 and 29.
	Descend 20 ft. over SW. slope, through moderate timber and dense undergrowth.
0.50	Ravine, drains S. 60° W.; asc. 35 ft. over NW. slope.
3.65	Spur, slopes SW.; desc. 140 ft. over SE. slope.
8.15	Ravine, drains S. 65° W.; asc. 120 ft. over N. slope.
11.75	Spur, slopes W.; desc. 155 ft. over S. slope.
15.40	Dirt road, 15 lks. wide, bears SE. and N. 60° W., in curve.
16.40	Creek, 1 lk. wide, course N. 40° W.; asc. 90 ft. over NE. slope.
20.15	Creek, 1 lk. wide, course N. 40° E.; asc. 295 ft. over NW. slope.
20.80	Dirt road, 15 lks. wide, bears N. and E., in curve.
35.50	Same dirt road, 15 lks. wide, bears E. and N. 30° W., in curve, also creek and culvert, course N. 15° E.; asc. 25 ft. over NW. slope.
38.61	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 S R 9 W $\frac{1}{4}$ S 29 S 28 1975
	from which
	A fir, 11 ins. diam., bears S. 1° E., 49 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
	A fir, 28 ins. diam., bears N. 25° W., 59 lks. dist., mkd. $\frac{1}{4}$ S29 BT.
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, bears N. 39° W., 14 lks. dist.
	Ascend 140 ft. over broken NE. slope.
49.65	Gravelled road, 30 lks. wide, bears E. and W.
57.915	Point for the S $\frac{1}{16}$ sec. cor. of secs. 28 and 29.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	S $\frac{1}{16}$ S 29 S 28 1975
	from which