

3.

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 65 ft. over SW. slope, through moderate timber and dense undergrowth.
1.50	Spur, slopes S. 75° W.; desc. 90 ft. over NW. slope.
5.65	Ravine, drains S. 65° W.; asc. 200 ft. over S. slope.
8.95	Spur, slopes W.; desc. 250 ft. over NW. slope.
18.10	Ravine, drains W.; asc. 510 ft. over SW. slope.
33.65	Spur, slopes S. 70° W.; asc. 5 ft. along W. slope.
38.00	The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, determined from the remains of the original bearing trees: <p style="margin-left: 40px;">A fir, 50 ins. diam., bears S. 52° E., 114 lks. dist., with scribe marks BT visible on open blaze. (Record, S. 54° E.)</p> <p style="margin-left: 40px;">A decayed fir snag, 38 ins. diam., bears S. 31° W., 28 lks. dist., with old axe marks visible on decayed blaze. (Record, S. 27° W.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">       T 22 S R 9 W  <math>\frac{1}{4}</math>        S 20   S 21        1975     </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears N. 55½° W., 54 lks. dist., mkd. <math>\frac{1}{4}</math> S20 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' E., beginning new measurement.</p> <p>Descend 60 ft. over NE. slope.</p>
8.50	Top of rock bluff, 40 ft. high, edge bears S. 60° E. and N. 60° W.
12.35	Ravine, drains S. 60° E.; desc. slightly along E. slope.
16.05	Ravine, drains S. 50° E.; desc. 20 ft. along E. slope.
23.95	Spur, slopes NE.; desc. 85 ft. over NE. slope.
25.30	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
34.90	Ravine, drains E.; desc. 30 ft. along broken E. slope.
37.40	Spur, slopes E.; desc. 55 ft. over NE. slope.
39.08	The cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by Harold T. Lewis, Registered Engineer, No. 722, in 1939, further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.