

16060

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>A maple, 26 ins. diam., bears S. 15° E., 8 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W ¼ S 16 S 21 1975</p> <p>from which new bearing trees</p> <p>A fir, 10 ins. diam., bears N. 38½° E., 30 lks. dist., mkd. ¼ S16 BT.</p> <p>A hemlock, 31 ins. diam., bears S. 26¾° W., 52 lks. dist., mkd. ¼ S21 BT.</p> <p>Corner is located on top of spur, slopes N. 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 39' W., beginning new measurement.</p> <p>Descend 10 ft. over NW. slope.</p> <p>0.95 Ravine, drains N. 10° E.; asc. 160 ft. over NE. slope.</p> <p>8.75 Spur, slopes NW.; desc. 240 ft. over SW. slope.</p> <p>14.25 Creek, 1 lk. wide, course N. 40° W.; desc. 10 ft. along N. slope.</p> <p>20.95 Creek, 1 lk. wide, course N. 70° E.; asc. 365 ft. over SE. slope.</p> <p>23.50 Top of rock bluff, 20 ft. high, edge bears N. and S.</p> <p>33.65 Spur, slopes S. 40° E.; desc. 10 ft. over SW. slope.</p> <p>35.70 Creek, 1 lk. wide, course S. 80° E.; asc. 60 ft. over NE. slope.</p> <p>39.76 The cor. of secs. 16, 17, 20, and 21.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, alder, cherry, and cedar; undergrowth, blackberry, fern, Oregon grape, vine maple, salal, elderberry, and huckleberry.</p> <hr/> <p>From the cor. of secs. 6 and 7 only, on the W. bdy. of sec. 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W S 6 S 8 S 7 1970</p> <p>from which the remains of the original bearing trees</p> <p>A fir stump, 20 ins. diam., bears N. 57° E., 66 lks. dist., with healed blaze.</p>