

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- A fir stump, 22 ins. diam., bears S. 65° E., 48 lks. dist., with illegible scribe marks visible on decayed blaze.
- A fir, 35 ins. diam., bears S. 58° W., 57 lks. dist., with healed blaze.
- A root hole, bears N. 54½° W., 171 lks. dist., with a down fir alongside, 44 ins. diam., no marks visible on decayed blaze.
- and the remains of bearing trees of which I have no record
- A fir stump, 19 ins. diam., bears N. 60½° E., 16 lks. dist., with fragmentary scribe marks visible on open blaze.
- A fir, 13 ins. diam., bears S. 80½° W., 29 lks. dist., with healed blaze.
- and a bearing tree mkd. by Jelley
- A fir, 13 ins. diam., bears N. 50½° W., 39 lks. dist., with healed blaze.
- N. 0° 43' W., along the E. bdy. of sec. 6.
- Ascend 20 ft. over SE. slope, through moderate timber and undergrowth.
- 2.50 Top of ascent, slopes E.; desc. 40 ft. over NE. slope.
- 3.59 Point for the closing cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 22 S R 9 W
S 6 | S 5 CC
 | S 8
 1974
- from which
- An alder, 12 ins. diam., bears N. 32½° E., 40 lks. dist., mkd. T22S R9W S5 CC BT.
- An alder, 9 ins. diam., bears S. 67° E., 68 lks. dist., mkd. T22S R9W S8 CC BT.
- Descend 50 ft. over NE. slope.
- 5.30 Creek, 3 lks. wide, course S. 70° E.; asc. 50 ft. over SE. slope.
- 6.60 Spur, slopes E.; desc. 25 ft. over NE. slope.
- 10.60 Ravine, drains N. 75° E.; asc. 30 ft. over SE. slope.
- 20.00 Spur, slopes E.; desc. 200 ft. over NE. slope.
- 36.20 Creek, 5 lks. wide, course N. 80° E.; asc. 20 ft. over SE. slope.
- 38.00 Spur, slopes S. 75° E.; desc. 30 ft. over NE. slope.