

16062

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

<p>CHAINS 39.80</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W $\frac{1}{4}$ S 6 1974</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 83° W., 89 lks. dist., mkd. $\frac{1}{4}$ S 6 BT.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 79° W., 65 lks. dist., mkd. $\frac{1}{4}$ S 6 BT.</p> <p>Ascend 100 ft. over SE. slope.</p>
<p>43.39</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W $\frac{1}{4}$ S 5 1974</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N. $16\frac{1}{2}^\circ$ E., 115 lks. dist., mkd. $\frac{1}{4}$ S 5 BT.</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears S. $24\frac{3}{4}^\circ$ E., 74 lks. dist., mkd. $\frac{1}{4}$ S 5 BT.</p> <p>Corner is located at top of ascent, slopes E.; desc. 150 ft. over NE. slope.</p>
<p>55.00</p>	<p>Creek, 3 lks. wide, course S. 30° E.; asc. 150 ft. over SW. slope.</p>
<p>59.70</p>	<p>Point for the N $\frac{1}{16}$ sec. cor. of sec. 6 only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N $\frac{1}{16}$ S 6 1974</p> <p>from which</p> <p style="padding-left: 40px;">A maple, 15 ins. diam., bears S. $28\frac{3}{4}^\circ$ W., 65 lks. dist., mkd. N $\frac{1}{16}$ S 6 BT.</p> <p style="padding-left: 40px;">A maple, 13 ins. diam., bears N. 54° W., 39 lks. dist., mkd. N $\frac{1}{16}$ S 6 BT.</p> <p>Ascend 65 ft. over SW. slope.</p>
<p>63.29</p>	<p>Point for the N $\frac{1}{16}$ sec. cor. of sec. 5 only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>