

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

N 1/16 S 5  
1974

from which

A maple, 11 ins. diam., bears N.  $63\frac{1}{2}^{\circ}$  E., 24 lks.  
dist., mkd. N 1/16 S5 BT.

A fir, 20 ins. diam., bears S.  $44^{\circ}$  E., 57 lks.  
dist., mkd. N 1/16 S5 BT.

Ascend 200 ft. over SW. slope.

77.53

Intersect the S. bdy. of sec. 31, T. 21 S., R. 9 W.

True point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 21 S R 9 W  
S 31  
S 6 | S 5  
C C  
T 22 S R 9 W  
1977

from which

A fir, 23 ins. diam., bears S.  $38^{\circ}$  E., 56 lks.  
dist., mkd. T22S R9W S5 CC BT.

A fir, 35 ins. diam., bears S.  $8\frac{1}{2}^{\circ}$  W., 35 lks.  
dist., mkd. T22S R9W S6 CC BT.

From this point, the cor. of secs. 31 and 32 only,  
T. 21 S., R. 9 W., bears S.  $89^{\circ} 53'$  E., 3.11 chs. dist.,  
hereinbefore described.

Ascend 5 ft. over SW. slope.

77.73

The original closing cor. of secs. 5 and 6, perpetuated  
and recorded by the County Surveyor, in 1971, monumented  
with an iron post, 2 ins. diam., firmly set, projecting  
4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S R  
S 31 9  
S 6 | S 5 W  
T 22 S  
C C  
1971

from which the remains of the original bearing trees

A root hole, bears S.  $2^{\circ}$  E., 307 lks. dist., with  
a down fir alongside, 36 ins. diam., no marks  
visible on decayed blaze.

A fir stump, 36 ins. diam., bears S.  $27\frac{1}{2}^{\circ}$  W., 90  
lks. dist., no marks visible on decayed blaze.

A fir stump, 36 ins. diam., bears N.  $17^{\circ}$  W., 65  
lks. dist., with scribe marks BT visible on  
open blaze.