

T. 20 S., R. 6½ W., Willamette Meridian, Oregon

CHAINS

The geographic position of the ¼ section corner of section 19 only, on the west boundary of township 20 south, range 6 west, as scaled from the Crow, Oregon, quadrangle map, published by the United States Geological Survey, in 1942, is as follows:

Latitude 43° 49.0' N. Longitude 123° 28.1' W.

The mean magnetic declination is 20° 05' E.

Dependent Resurvey of a Portion of the West Boundary,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by John H. McClung,
U. S. Deputy Surveyor, in 1872,
and the resurvey by Thomas E. Todd,
U. S. Deputy Surveyor, in 1891)

Beginning at the ¼ sec. cor. of sec. 19 only, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

DOUG CO SURVEYORS OFFICE

T 20 S
W ¼ | S 19
R 7 W | R 6 W
1962

from which the remaining original bearing tree

A fir, 26 ins. diam., bears N. 5° W., 20 lks. dist., with scribe mark 4 visible on opened blaze.

and a bearing tree mkd. by Godfrey

A fir, 30 ins. diam., bears N. 77° E., 22 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside iron post.

N. 0° 28' E., on the W. bdy. of sec. 19, marking and blazing the true line.

Ascend 265 ft. over SE. slope, through heavy timber and dense undergrowth.

- 8.40 Spur ridge, bears N. 65° E. and S. 65° W.; desc. 310 ft. over NW. slope.
- 22.00 Ravine drains N. 45° W.; asc. 65 ft. over SW. slope.
- 30.20 Spur, slopes N. 30° W.; desc. 280 ft. over NE. slope.
- 36.56 True point for the cor. of secs. 13 and 24 only, on the E. bdy. of T. 20 S., R. 7 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.