

16069

Dependent Resurvey of a Portion of the West Boundary,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

T 20 S	T 20 S
S 13	R 6 W
S 24	S 19
R 7 W	
1978	

from which

A twin maple, 9 ins. diam., bears N. 32° W., 59 lks. dist., mkd. T20S R7W S13 BT.

An alder, 8 ins. diam., bears S. 49½° W., 33 lks. dist., mkd. T20S R7W S24 BT.

Set a 5 ft. steel fence post alongside iron post.

From this point, the original cor. of secs. 13 and 24, bears East, 0.040 chs. dist., perpetuated and recorded by John D. Venator, Registered Land Surveyor No. 278, in 1954, and further perpetuated and recorded by Wayne R. Tinglum, Engineering Technician for the Bureau of Land Management, in 1976, monumented with an iron rod, ¾ in. diam., firmly set, projecting 6 ins. above ground, from which the remains of a bearing tree mkd. by Todd:

A cedar stump, 20 ins. diam., bears N. 61° W., 12 lks. dist., with scribe marks BT visible on decayed blaze. (Record, N. 8° W.)

and bearing trees mkd. by Tinglum

An alder, 8 ins. diam., bears N. 74° W., 31 lks. dist., with scribe marks T20S R7W S13 BT visible on bark.

An alder, 7 ins. diam., bears S. 17½° W., 28 lks. dist., with scribe marks T20S R7W S24 BT visible on bark.

Bury iron rod at original corner position.

Descend 20 ft. over NE. slope.

37.45 Creek, 2 lks. wide, course N. 40° W.; asc. 20 ft. over SW. slope.

39.02 The cor. of secs. 18 and 19 only, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

DOUG CO SURVEYORS OFFICE

T 20 S	
S 18	
S 19	
R 7 W	R 6 W
1962	

from which the remains of bearing trees mkd. by Todd

A fir snag, 56 ins. diam., bears N. 5° E., 60 lks. dist., no marks visible on decayed blaze.

A root hole, bears S. 63° E., 35 lks. dist., with a down and decayed hemlock alongside, size indeterminate, no marks visible.