

16071

Dependent Resurvey of a Portion of the West Boundary,
T. 20 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 20 S
R 6½ W R 6 W
½
S 13 | S 18
1978

from which new bearing trees

A hemlock, 14 ins. diam., bears N. 27° E., 73½ lks. dist., mkd. ¼ S18 BT.

A fir, 33 ins. diam., bears N. 18° W., 62 lks. dist., mkd. ¼ S13 BT.

Reset steel shaft and set a 5 ft. steel fence post alongside iron post.

N. 10° 53' E., beginning new measurement.

Descend 15 ft. over NW. slope.

- 0.45 Creek, 3 lks. wide, course W.; asc. 50 ft. over SW. slope.
- 12.60 Spur, slopes W.; desc. 45 ft. over NW. slope.
- 14.30 Creek, 3 lks. wide, course S. 75° W.; asc. 60 ft. over SW. slope.
- 19.50 Spur, slopes W.; desc. 30 ft. over NW. slope.
- 21.60 Creek, 3 lks. wide, course W.; asc. 235 ft. over SW. slope.
- 37.70 Spur, slopes W.; desc. 60 ft. over N. slope.
- 39.40 Ravine, drains W.; asc. 180 ft. over SW. slope.
- 43.97 The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 28 ins. long, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 20 S
R 6 W
S 7
S 18
1962

from which the remains of the original bearing trees

A fir, 63 ins. diam., bears N. 4° W., 11 lks. dist., with healed blaze.

A fir snag, 28 ins. diam., bears S. 35° E., 21 lks. dist., no marks visible on opened blaze.

A fir snag, 70 ins. diam., bears S. 34° W., 105 lks. dist., no marks visible.

and a bearing tree mkd. by Lyle E. Boustead, Land Agent for Weyerhaeuser Timber Company, in 1958