

Dependent Resurvey of a Portion of the West Boundary,  
T. 20 S., R. 6 W., Willamette Meridian, Oregon

## CHAINS

A fir, 24 ins. diam., bears N. 82° W., 51½ lks. dist., with a galvanized nail with "W" embossed on head, at base.

and bearing trees mkd. by Glenn

A fir, 44 ins. diam., bears N. 85¼° E., 89½ lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 62½° E., 241 lks. dist., with healed blaze.

Add marks R6½W S12 S13 1978 to brass cap.

No other suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, alder, dogwood, and chinquapin; undergrowth, vine maple, hazel, arrowwood huckleberry, Oregon grape, salal, blackberry, and fern.

N. 2° 20' W., bet. secs. 7 and 12.

Ascend 100 ft. over SW. slope, through heavy timber and dense undergrowth.

- 4.40 Dirt road, 20 lks. wide, on top of ridge, bears N. 75° W. and S. 75° E.; desc. 400 ft. over NW. slope.
- 12.30 Creek, 3 lks. wide, course N. 50° E.; asc. 65 ft. over SE. slope.
- 16.90 Spur, slopes E.; desc. 175 ft. over NE. slope.
- 22.50 Creek, 4 lks. wide, course N. 70° E.; asc. 55 ft. over SE. slope.
- 25.60 Spur, slopes E.; desc. 95 ft. over NE. slope.
- 27.40 Creek, 2 lks. wide, course E.; asc. 365 ft. over SE. slope.
- 35.40 Spur, slopes N. 60° E.; desc. 170 ft. over N. slope.
- 40.95 Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 20 S  
R 6½ W R 6 W  
¼  
S 12 | S 7  
1978

from which

A fir, 53 ins. diam., bears N. 36° E., 57 lks. dist., mkd. ¼ S7 BT.

A hemlock, 16 ins. diam., bears S. 61¼° W., 23½ lks. dist., mkd. ¼ S12 BT.