

309

Dependent Resurvey of a Portion of the South Boundary,
T. 19 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
12.30	Creek, 2 lks. wide, course S. 15° E.; asc. 45 ft. over SE. slope.
13.02	True point for the closing cor. of Tps. 20 S., Rs. 6½ and 7 W., hereinafter described. Ascend 300 ft. over SE. slope.
22.50	Spur, slopes N. 85° E.; asc. 220 ft. over broken NE. slope near top of spur.
37.80	Top of mountain, from which ridges bear N., S., and W.; desc. 35 ft. along top of ridge, also enter timber, edge bears N. and S.
39.68	The ¼ sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	$\frac{1}{4} S 36$ 1949
	from which the remains of bearing trees mkd. by Price and Tillman
	A sawed fir stump, 38 ins. diam., bears N. 30° E., 18 lks. dist., with scribe marks ¼ S36 BT visible on open blaze.
	A sawed fir stump, 72 ins. diam., bears N. 77½° W., 71 lks. dist., with healed blaze.
	and new bearing trees
	A fir, 13 ins. diam., bears N. 16° E., 14 lks. dist., mkd. ¼ S36 BT.
	A fir, 10 ins. diam., bears N. 51° W., 6 lks. dist., mkd. ¼ S36 BT.
	Set a 5 ft. steel fence post alongside iron post.
	Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, alder, chinquapin, madrone, and dogwood; undergrowth, ceanothus, manzanita, vine maple, hazel, arrowwood, huckleberry, Oregon grape, salal, and fern.
Dependent Resurvey of a Portion of the East Boundary, T. 20 S., R. 7 W., Willamette Meridian, Oregon	
(Restoring the survey by Thomas E. Todd, U. S. Deputy Surveyor, in 1891)	
From the cor. of secs. 18 and 19 only, T. 20 S., R. 6 W., hereinbefore described.	
N. 0° 17' E., on the E. bdy. of sec. 13, marking and blazing the true line.	
Ascend 90 ft. over SW. slope, through heavy timber and dense undergrowth.	
5.50	Spur, slopes W.; desc. 150 ft. over NW. slope.