

16077

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
8.50	Dry creek bed, 5 lks. wide, course N. 60° W.; desc. 15 ft. along creek bottom.
17.80	Panther Creek, 10 lks. wide, course S. 25° W.; asc. 60 ft. along creek bottom.
26.00	Gravelled road, 25 lks. wide, bears N. 30° E. and S. 30° W.
27.70	Creek, 2 lks. wide, course S. 60° E.; asc. 170 ft. over SE. slope.
36.70	Spur, slopes S. 80° E.; desc. 10 ft. over NE. slope.
39.07	The $\frac{1}{4}$ sec. cor. of sec. 13 only, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	DOUG CO SURVEYORS OFFICE T 20 S $\frac{1}{4}$ S 13 1962
	from which the original bearing trees
	A fir, 32 ins. diam., bears East, 33 lks. dist., with healed blaze. (Record, 36 lks.)
	A fir, 45 ins. diam., bears N. 67° W., 59 lks. dist., with healed blaze. (Record, 64 lks.)
	and a bearing tree mkd. by Godfrey
	A fir, 16 ins. diam., bears S. 16° W., 16 lks. dist., with healed blaze.
	—————
	N. 0° 12' W., beginning new measurement.
	Descend 120 ft. over NE. slope.
4.10	Point for the $\frac{1}{4}$ sec. cor. of sec. 13 only, T. 20 S., R. 6 $\frac{1}{2}$ W., hereinafter described.
	Descend 55 ft. over NE. slope.
5.60	Creek, 3 lks. wide, course S. 40° E.; asc. 330 ft. over SW. slope.
19.10	Spur, slopes S. 40° E.; desc. 20 ft. over NE. slope.
20.30	Ravine, drains S. 40° E.; asc. 140 ft. over S. slope.
25.00	Spur, slopes S. 80° E.; desc. 195 ft. over NE. slope.
29.40	Creek, 2 lks. wide, course N. 80° E.; asc. 230 ft. over SE. slope.
35.60	Spur, slopes E.; desc. 50 ft. over NE. slope:
36.72	The cor. of secs. 12 and 13 only, perpetuated and recorded by David M. Thompson, Registered Land Surveyor No. 911, in 1973, monumented with an iron rod, $\frac{3}{8}$ in. diam., firmly set, projecting 2 ins. above ground, from which the remains of the original bearing trees: