

Dependent Resurvey of a Portion of the East Boundary,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

A fir, 36 ins. diam., bears N. 37° E., 60 lks.  
dist., with healed blaze. (Record, N. 27° E.)

A fir, 40 ins. diam., bears N. 30° W., 9 lks.  
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 20 S	T 20 S
S 12	R 6½ W
S 13	S 13
R 7 W	
	1978

from which a new bearing tree

A hemlock, 7 ins. diam., bears S. 21° W., 11 lks.  
dist., mkd. T20S R7W S13 BT.

Reset iron rod and set a 5 ft. steel fence post  
alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, alder, madrone,  
chinquapin, and dogwood; undergrowth, vine maple, hazel,  
arrowwood, huckleberry, blackberry, Oregon grape, salal,  
and fern.

N. 0° 03' E., on the E. bdy. of sec. 12.

Descend 160 ft. over NE. slope, through heavy timber and  
dense undergrowth.

3.05 Creek, 3 lks. wide, course N. 80° E.; asc. 115 ft. over  
SE. slope.

7.20 Spur, slopes E.; desc. 145 ft. over NE. slope.

10.55 Point for the closing cor. of secs. 12 and 13, T. 20 S.,  
R. 6½ W., hereinafter described.

Descend 85 ft. over NE. slope.

12.60 Creek, 5 lks. wide, course S. 80° E.; asc. 200 ft. over  
S. slope.

18.75 An original line tree; a fir, 65 ins. diam., with 2  
notches on N. and S. faces.

N. 0° 04' E., beginning new measurement.

Ascend 25 ft. over S. slope.

0.67 Point for the S 1/16 sec. cor. of sec. 12 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

S 1/16	
S 12	
	1977