

16079

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p>A fir, 74 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 56 lks. dist., mkd. S 1/16 S12 BT.</p> <p>A hemlock, 16 ins. diam., bears N. 69° W., $30\frac{1}{2}$ lks. dist., mkd. S 1/16 S12 BT.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p> <p>Ascend 20 ft. over S. slope.</p>
1.70	Dirt road, 15 lks. wide, on top of ridge, bears N. 70° W. and S. 70° E.; desc. 80 ft. over NE. slope.
3.80	Ravine, drains E.; asc. 115 ft. over SE. slope.
9.30	Spur, slopes N. 65° E.; desc. 330 ft. over NE. slope.
15.60	Creek, 3 lks. wide, course N. 80° E.; asc. 200 ft. over SE. slope.
19.81	<p>The $\frac{1}{4}$ sec. cor. of sec. 12 only, perpetuated and recorded by David M. Thompson, Registered Land Surveyor No. 911, in 1973, monumented with the original sandstone, 20 x 14 x 4 ins., firmly set, 18 ins. in the ground, mkd. $\frac{1}{4}$ on W. face and X on top, with an iron rod $\frac{3}{8}$ in. diam., firmly set flush with the ground alongside, from which the remains of the original bearing trees:</p> <p>A fir, 30 ins. diam., bears East, 13 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Thompson</p> <p>A fir, 32 ins. diam., bears S. 52° W., 66 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 20 S R 7 W R $6\frac{1}{2}$ W $\frac{1}{4}$ S 12 1977</p> </div> <p>Deposit corner stone and reset iron rod, and set a 5 ft. steel fence post alongside iron post.</p> <hr/> <p>N. $0^{\circ} 01'$ E., beginning new measurement.</p> <p>Ascend 135 ft. over SE. slope.</p>
3.90	Spur, slopes N. 60° E.; desc. 325 ft. over NE. slope.
10.00	Creek, 2 lks. wide, course N. 75° E.; asc. 115 ft. over SE. slope.
12.89	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 12 only, T. 20 S., R. $6\frac{1}{2}$ W., hereinafter described.</p> <p>Ascend 150 ft. over SE. slope.</p>
15.80	Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.