

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

<p>CHAINS 18.00</p>	<p>Spur ridge, bears N. 70° E. and S. 70° W.; desc. 70 ft. over N. slope.</p>
<p>19.875</p>	<p>Point for the N 1/16 sec. cor. of sec. 12 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">N 1/16 S 12 1977</p>
	<p>from which</p> <p>A cedar, 22 ins. diam., bears S. 78¾° W., 23 lks. dist., mkd. N 1/16 S12 BT.</p> <p>A fir, 72 ins. diam., bears N. 21½° W., 87 lks. dist., mkd. N 1/16 S12 BT.</p> <p>Set a 5 ft. steel fence post alongside iron post.</p>
	<p>Descend 280 ft. over N. slope.</p>
<p>32.10</p>	<p>Creek, 4 lks. wide, course N. 60° E.; asc. 175 ft. over SE. slope.</p>
<p>39.75</p>	<p>The cor. of secs. 1 and 12 only, perpetuated and recorded by David M. Thompson, Registered Land Surveyor No. 911, in 1973, monumented with an iron rod, ¾ in. diam., firmly set, projecting 2 ins. above ground, from which the remains of the original bearing trees:</p>
	<p>A fir, 54 ins. diam., bears N. 22° E., 55 lks. dist., with healed blaze. (Record, 59 lks.)</p>
	<p>A fir, 32 ins. diam., bears S. 16° E., 99 lks. dist., with healed blaze. (Record, 106 lks.)</p>
	<p>A fir, 55 ins. diam., bears S. 1½° W., 59 lks. dist., with healed blaze. (Record, 61 lks.)</p>
	<p>A fir snag, 53 ins. diam., bears N. 85° W., 260 lks. dist., with healed blaze. (Record, 206 lks.)</p>
	<p>and a bearing tree mkd. by Thompson</p>
	<p>A fir, 21 ins. diam., bears N. 70° W., 19 lks. dist., with scribe marks R7W visible on open blaze.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 20 S T 20 S S 1 R 6½ W S 12 S 12 R 7 W 1976</p>
	<p>Land, mountainous. Soil, rocky clay.</p>