

16081

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	<p>Timber, fir, hemlock, cedar, yew, maple, alder, madrone, chinquapin, and dogwood; undergrowth, vine maple, hazel, arrowwood, huckleberry, blackberry, Oregon grape, salal, and fern.</p>
	<p>N. 0° 02' W., on the E. bdy. of sec. 1.</p> <p>Ascend 255 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
8.60	Spur, slopes S. 70° E.; desc. 175 ft. over NE. slope.
13.00	Creek, 2 lks. wide, course N. 70° E.; asc. 20 ft. over SE. slope.
14.05	Point for the closing cor. of secs. 1 and 12, T. 20 S., R. 6½ W., hereinafter described.
	Ascend 245 ft. over SE. slope.
28.30	Spur ridge, bears E. and S. 70° W.; desc. 125 ft. over NE. slope.
29.00	Dirt road, 15 lks. wide, bears S. 80° E. and N. 80° W., curving N.
39.15	<p>The ¼ sec. cor. of sec. 1 only, determined from the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A sawed fir stump, 34 ins. diam., bears S. 10° W., 23 lks. dist., with scribe marks ¼ S visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>T 20 S R 7 W R 6½ W ¼ S 1 1978</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 20½° W., 26½ lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 39½° W., 33 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">Set a 5 ft. steel fence post alongside iron post.</p>
	<p>N. 0° 07' W., beginning new measurement.</p> <p>Descend 20 ft. over NE. slope.</p>
0.80	Ravine, drains E.; asc. 40 ft. over SE. slope.
5.30	Dirt road, 15 lks. wide, on top of spur ridge, bears E. and W.; desc. 245 ft. over NW. slope.
14.90	Point for the ¼ sec. cor. of sec. 1 only, T. 20 S., R. 6½ W., hereinafter described.
	Descend 305 ft. over NW. slope.