

315

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
21.80 Creek, 3 lks. wide, course S. 80° E.; asc. 485 ft. over S. slope.

36.80 Spur, slopes E.; desc. 400 ft. over NE. slope.

47.90 Creek, 4 lks. wide, course N. 80° E.; asc. 25 ft. over SE. slope.

49.77 Intersect the S. bdy. of T. 19 S., R. 7 W.

True point for the closing cor. of T. 20 S., Rs. 6½ and 7 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S R 7 W
S 36
S 1 | S 1
R 7 W | R 6½ W
T 20 S
CC
1978

from which

A fir, 8 ins. diam., bears S. 62½° W., 48 lks. dist., mkd. T20S R7W S1 CC BT.

No other suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

From this point, the cor. of Tps. 19 and 20 S., Rs. 6, 6½, and 7 W., bears N. 89° 49' E., 13.02 chs. dist., hereinbefore described.

Ascend slightly over SE. slope.

50.19 The original closing cor. of T. 20 S., Rs. 6 and 7 W., monumented with an iron rod, ¾ in. diam., loosely set, projecting 30 ins. above ground, from which the remains of the original bearing trees:

A root hole, bears S. 40° W., 30 lks. dist., with a down fir alongside, 48 ins. diam., with healed blaze.

A maple clump, bears N. 7° W., 60 lks. dist.

and the remains of bearing trees mkd. by the County Surveyor, date unknown

A sawed fir stump, 60 ins. diam., bears S. 4° E., 109 lks. dist., with healed blaze.

A sawed fir stump, 14 ins. diam., bears S. 13° W., 117 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, alder, madrone, chinquapin, and dogwood; undergrowth, vine maple, hazel, arrowwood, huckleberry, blackberry, Oregon grape, salal, and fern.