

16683

T. 20 S., R. 6½ W., Willamette Meridian, Oregon

CHAINS

Survey of the Subdivisional Lines,
T. 20 S., R. 6½ W., Willamette Meridian, Oregon

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.

West, bet. secs. 12 and 13, marking and blazing the true line.

Descend 300 ft. over SW. slope, through heavy timber and dense undergrowth.

12.75 Creek, 3 lks. wide, course S. 40° E.; asc. 105 ft. over NW. slope.

16.58 Intersect the E. bdy. of T. 20 S., R. 7 W.

Point for the closing cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S		T 20 S	
R 7 W		S 12	
S 12		S 13	CC
		R 6½ W	
		1978	

from which

A hemlock, 11 ins. diam., bears N. 74° E., 44 lks. dist., mkd. T20S R6½W S12 CC BT.

A fir, 30 ins. diam., bears S. 85° E., 10 lks. dist., mkd. T20S R6½W S13 CC BT.

Set a 5 ft. steel fence post alongside iron post.

From this point, the cor. of secs. 12 and 13 only, T. 20 S., R. 7 W., bears S. 0° 03' W., 10.55 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, alder, madrone, chinquapin, and dogwood; undergrowth, vine maple, hazel, arrowwood, huckleberry, blackberry, Oregon grape, salal, and fern.

To complete the survey of sec. 13, I return to the ¼ sec. cor. of sec. 13 only, T. 20 S., R. 7 W., and run

N. 0° 12' W., on the W. bdy. of sec. 13.

4.10 Point for the ¼ sec. cor. of sec. 13 only, at midpoint on the W. bdy. of sec. 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 20 S	
R 7 W	R 6½ W
	¼ S 13
	1978

from which