

16685

Survey of the Subdivisional Lines,
T. 20 S., R. 6½ W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S
R 7 W | R 6½ W
 | ½ S 12
 1978

from which

A fir, 5 ins. diam., bears N. 47° E., 25 lks. dist., mkd. X BT.

No other suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

To complete the survey of sec. 1, I return to the ¼ sec. cor. of sec. 1 only, T. 20 S., R. 7 W., and run

N. 0° 07' W., on the W. bdy. of sec. 1.

14.90

Point for the ¼ sec. cor. of sec. 1 only, 40.00 chs. latitudinally from the closing cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S
R 7 W | R 6½ W
 | ½ S 1
 1978

from which

A fir, 20 ins. diam., bears N. 5° E., 10 lks. dist., mkd. ½ S1 BT.

A fir, 25 ins. diam., bears S. 69° E., 18 lks. dist., mkd. ½ S1 BT.

Set a 5 ft. steel fence post alongside iron post.

GENERAL DESCRIPTION

The lands included in the foregoing survey are located in the Coast Range approximately 25 miles southwest of Eugene, Oregon. The area is drained primarily by the Siuslaw River on the north, Smith River on the south, and several small tributaries flowing into these rivers. The elevations range from about 800 feet above sea level on Panther Creek in section 13, to about 1,250 feet above sea level in the southern portion of section 1.

Access is gained by way of Oxbow Road, a paved Bureau of Land Management access road, and numerous gravelled and dirt logging roads.

Soil is composed of rocky clay, from a few inches deep at the higher elevations, with some sandy loam along the river bottom with a depth of several feet. The soil is suited primarily for the growing of timber, with timber harvesting and recreation being the chief activities of the area. Timber consists primarily of fir, hemlock, alder, and maple, with some cedar, yew, madrone,