

## T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 13, 14, 23, and 24, as scaled from the Crow, Oregon, quadrangle map, published by the United States Geological Survey, in 1942, is as follows:

Latitude 43° 49.4' N. Longitude 123° 29.4' W.

The mean magnetic declination is 20° 05' E.

Dependent Resurvey of a Portion of the East Boundary,  
T. 20 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by William P. Wright,  
U. S. Deputy Surveyor, in 1883,  
the resurvey by Thomas A. Tillman,  
Raymond M. Bicknell, Hans W. Thielsen,  
and Joseph S. Gawron, Cadastral Surveyors, in 1953-54,  
and the rehabilitation of certain original corners by  
William W. Glenn, C. Albert White, and James E. Jelley,  
Cadastral Surveyors, in 1967)

Beginning at the cor. of secs. 1 and 12 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, and in a mound of stone, 2 ft. base, 10 ins. high, with brass cap mkd.

T 20 S	T 20 S
S 1	R 7 W
S 12	S 7
R 8 W	
	1954

from which the remains of an original bearing tree

A root hole, bears N. 47° E., 38 lks. dist., with a down fir alongside, 50 ins. diam., with healed blaze.

and the remains of bearing trees mkd. by Tillman, Bicknell, Thielsen, and Gawron, and rescribed by Glenn, White, and Jelley

A fir, 65 ins. diam., bears S. 87½° W., 37 lks. dist., with fragmentary scribe marks visible on burned and partially healed blaze, and rescribed T20S R8W S12 BT.

A sawed fir stump, 60 ins. diam., bears N. 36½° W., 64 lks. dist., no marks visible on open and burned blaze, and rescribed T20S R8W S1 BT.

No suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

N. 1° 18' E., on the E. bdy. of sec. 1, marking and blazing the true line.

Descend 140 ft. over broken N. slope, across burned area, through dense undergrowth.

3.95

North Sister Creek, 2 lks. wide, course W.; asc. 195 ft. over SW. slope.