

16090

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
9.50	Gravelled road, 25 lks. wide, bears E. and W., curving SW.
12.60	Creek, 1 lk. wide, course S. 10° W., from N.; asc. 45 ft. along creek.
14.50	Leave creek, 1 lk. wide, course S., from N. 45° E.; asc. 110 ft. over SE. slope.
17.43	True point for the closing cor. of secs. 6 and 7, T. 20 S., R. 7 W., hereinafter described. Ascend 250 ft. over SE. slope, changing to S. slope.
19.70	Gravelled road, 25 lks. wide, bears N. 85° W., and S. 85° E.
22.60	Gravelled road, 30 lks. wide, bears N. 80° W. and E.
30.20	Ridge, bears N. 80° W. and S. 80° E., also leave burned area, edge bears same; desc. 220 ft. over N. slope.
39.44	The $\frac{1}{4}$ sec. cor. of sec. 1 only, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. $\frac{1}{4}$ S 1 1954 from which the remains of bearing trees mkd. by Tillman, Bicknell, Thielsen, and Gawron A sawed fir stump, 12 ins. diam., bears S. 51° W., 31 lks. dist., with healed blaze. A sawed fir stump, 15 ins. diam., bears N. 19° W., 24 lks. dist., with healed blaze. and a bearing tree described by Glenn, White, and Jelley A sawed fir stump, 16 ins. diam., bears N. 38 $\frac{1}{2}$ ° E., 19 lks. dist., with healed blaze. and the only remaining bearing tree mkd. by Glenn, White, and Jelley A fir, 15 ins. diam., bears S. 29° W., 156 lks. dist., with healed blaze. No suitable trees available within limits. Set a 5 ft. steel fence post alongside iron post. N. 0° 58' E., beginning new measurement. Ascend 15 ft. over SE. slope.
1.50	Spur, slopes NE., also gravelled road, 20 lks. wide, bears NE. and SW.; desc. 475 ft. over NW. slope.
12.40	Dry creek bed, 5 lks. wide, course N. 50° E.; asc. 100 ft. over SE. slope.
15.30	Spur, slopes E.; desc. 35 ft. over NE. slope.
17.67	Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 20 S., R. 7 W., at proportionate distance on the W. bdy. of sec. 6.