

16032

Dependent Resurvey of a Portion of the East Boundary,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Charles M. Collier,
U. S. Deputy Surveyor, in 1891,
and the resurvey by Norman D. Price and
Thomas A. Tillman, Cadastral Engineers, in 1949)

From the cor. of Tps. 19 and 20 S., R. 8 W.

N. 0° 10' E., on the E. bdy. of sec. 36, marking and
blazing the true line.

Ascend 145 ft. over SW. slope, through heavy timber and
dense undergrowth.

3.50 Spur, slopes SE.; asc. 40 ft. along broken E. slope.

7.30 Head of ravine, drains S. 50° E.; asc. 165 ft. over SW.
slope.

13.30 Spur, slopes SE.; desc. 75 ft. over NE. slope.

16.90 Creek, 2 lks. wide, course SE.; asc. 35 ft. over S.
slope.

17.75 Point for the 80 1/16 sec. cor. of sec. 6 only,
T. 20 S., R. 7 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

1/16
S 6
80
1977

from which

A fir, 28 ins. diam., bears N. 63° E., 35 lks.
dist., mkd. 80 1/16 S6 BT.

A maple, 15 ins. diam., bears S. 49° E., 80 lks.
dist., mkd. 80 1/16 S6 BT.

Set a 5 ft. steel fence post alongside iron post.

Ascend 375 ft. over S. slope.

23.40 Gravelled road, 20 lks. wide, bears N. 70° E. and
S. 70° W.

27.60 Top of ascent, slopes E.; desc. 10 ft. along E. slope.

28.80 Ridge, bears N. and S. 30° W.; desc. 70 ft. along
ridge top.

34.71 The closing cor. of Tps. 19 and 20 S., R. 7 W., monument-
ed with an iron post, 3 ins. diam., firmly set, project-
ing 10 ins. above ground, with brass cap mkd.

T 19 S	T 19 S
	R 7 W
S 36	S 31 CC
	S 6
R 8 W	T 20 S
	1949

from which the remains of bearing trees mkd. by Price
and Tillman