

Dependent Resurvey of a Portion of the East Boundary,  
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 60 ins. diam., bears N.  $11\frac{1}{2}^{\circ}$  E., 35  
lks. dist., with healed blaze.

A hemlock, 31 ins. diam., bears S.  $31^{\circ}$  E., 62  
lks. dist., with healed blaze.

and a new bearing tree

A fir, 20 ins. diam., bears N.  $41\frac{1}{2}^{\circ}$  E.,  $50\frac{1}{2}$  lks.  
dist., mkd. T19S R7W S31 CC BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located in saddle of ridge, bears N. and S.

Ascend 25 ft. along ridge top.

39.47

The  $\frac{1}{4}$  sec. cor. of sec. 36 only, monumented with an iron  
post, 1 in. diam., firmly set, projecting 6 ins. above  
ground, with brass cap mkd.

$\frac{1}{4}$  S 36|  
1949

from which an original bearing tree

A fir, 48 ins. diam., bears S.  $45\frac{1}{2}^{\circ}$  E., 22 lks.  
dist., with healed blaze.

and the remains of bearing trees mkd. by Price and  
Tillman

A root hole, bears S.  $46\frac{1}{2}^{\circ}$  W., 161 lks. dist., with  
a down fir alongside, 30 ins. diam., with  
fragmentary scribe marks visible on decayed  
blaze.

A fir, 49 ins. diam., bears N.  $64^{\circ}$  W., 35 lks.  
dist., with healed blaze.

and a new bearing tree

A fir, 17 ins. diam., bears S.  $35\frac{1}{2}^{\circ}$  W., 127 lks.  
dist., mkd.  $\frac{1}{4}$  S36 BT.

Set a 5 ft. steel fence post alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, alder, chinquapin,  
and dogwood; undergrowth, ceanothus, manzanita, vine  
maple, hazel, arrowwood, huckleberry, Oregon grape,  
salal, and fern.

Dependent Resurvey of a Portion of the South Boundary,  
T. 19 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Henry C. and Joseph Perkins,  
U. S. Deputy Surveyors, in 1874,  
the survey and resurvey by Thomas E. Todd,  
U. S. Deputy Surveyor, in 1891,  
and the resurvey by Norman D. Price and  
Thomas A. Tillman, Cadastral Engineers, in 1949)