

Dependent Resurvey of a Portion of the South Boundary,  
T. 19 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	N. 89° 36' W., on the S. bdy. of sec. 35.
	Descend 65 ft. over SW. slope, through medium timber and dense undergrowth.
12.30	Spur ridge, bears NE. and SW.; desc. 25 ft. over NW. slope.
13.12	True point for the closing cor. of secs. 1 and 2, T. 20 S., R. 7 W., hereinafter described.
	Descend 330 ft. over NW. slope, changing to W. slope.
14.00	Gravelled road, 15 lks. wide, bears N. 30° E. and S. 10° W., in curve.
20.60	Ravine, drains W., from S. 45° E.; desc. 130 ft. along ravine.
25.85	Leave ravine, drains S. 70° W.; asc. 15 ft. along S. slope.
29.70	Top of ascent, slopes S.; desc. 135 ft. over SW. slope.
34.50	Gravelled road, 15 lks. wide, bears N. and S.
39.00	Haight Creek, 8 lks. wide, course N.; asc. 20 ft. over E. slope.
39.37	The $\frac{1}{4}$ sec. cor. of sec. 35 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<u><math>\frac{1}{4}</math> S 35</u> 1949
	from which the remains of bearing trees mkd. by Price and Tillman
	A sawed white fir stump, 17 ins. diam., bears N. 16 $\frac{1}{2}$ ° E., 115 lks. dist., with scribe marks BT visible on open blaze. (Record, 113 lks.)
	A maple, 40 ins. diam., bears N. 61° W., 78 lks. dist., with healed blaze. (Record, 76 lks.)
	and a new bearing tree
	An alder, 9 ins. diam., bears N. 9 $\frac{1}{2}$ ° E., 41 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	Set a 5 ft. steel fence post alongside iron post.
	—————
	N. 89° 41' W., beginning new measurement.
	Ascend 100 ft. over E. slope.
1.30	Paved road, 25 lks. wide, bears N. and S.
4.30	Top of ascent, slopes N.; desc. 5 ft. along N. slope.
7.50	Ravine, drains N. 70° E.; asc. 170 ft. over SE. slope.
12.33	Point for the $\frac{1}{4}$ sec. cor. of sec. 2 only, T. 20 S., R. 7 W., hereinafter described.