

337

Dependent Resurvey of a Portion of the South Boundary,
T. 19 S., R. 7 W., Willamette Meridian, Oregon

CHAINS 39.16	<p>The $\frac{1}{4}$ sec. cor. of sec. 32 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;"><u>$\frac{1}{4}$ S 32</u> 1949</p>
	<p>from which the original bearing trees</p>
	<p>A fir, 68 ins. diam., bears S. 10° E., 50 lks. dist., with healed blaze.</p>
	<p>A fir, 37 ins. diam., bears N. 30° W., 10 lks. dist., with healed blaze.</p>
	<p>and a bearing tree mkd. by Price and Tillman</p>
	<p>A fir, 37 ins. diam., bears N. 59° E., 105 lks. dist., with healed blaze.</p>
	<p>Set a 5 ft. steel fence post alongside iron post.</p>
	<p>S. $89^{\circ} 50'$ W., beginning new measurement.</p>
	<p>Descend 170 ft. over NW. slope, changing to steep W. slope.</p>
3.30	<p>Dry creek bed, 4 lks. wide, course N.; asc. 315 ft. over steep E. slope.</p>
9.25	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, T. 20 S., R. 7 W., at midpoint on the N. bdy. of sec. 5.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 19 S R 7 W <u>$\frac{1}{4}$ S 5</u> T 20 S R 7 W 1977</p>
	<p>from which</p>
	<p>A fir, 15 ins. diam., bears S. 5° E., 36 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p>
	<p>A fir, 20 ins. diam., bears S. $71\frac{1}{2}^{\circ}$ W., 32 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p>
	<p>Set a 5 ft. steel fence post alongside iron post.</p>
	<p>Corner is located on spur, slopes N. 35° E.</p>
	<p>Descend 115 ft. over NW. slope.</p>
13.80	<p>Ravine, drains N. 30° E.; asc. 225 ft. over steep E. slope.</p>
18.40	<p>Spur, slopes N.; desc. 265 ft. over steep NW. slope.</p>
23.90	<p>Creek, 1 lk. wide, course N. 10° E.; asc. 365 ft. over steep E. slope.</p>
31.40	<p>Spur, slopes N.; desc. 90 ft. over NW. slope.</p>